



# TASKI®

# Strip Eze



# F1

## Stripper

### Description

TASKI® Strip Eze is a deep penetrating non-ammoniated stripper for resilient and non-resilient floors. TASKI® Strip Eze is an economical stripper for all general purpose stripping.

### Features

- Economical stripper for all general purpose stripping.
- Deep penetrating.
- Removes metalised and non –metalised floor sealers and finishes.

### Benefits

- Non ammoniated means less fumes.
- Low foaming formulation for easy pick up.
- Effective on a wide range of water based sealer/finishes.

### Application areas

- Retail
- Education
- Government
- Healthcare
- Institutional Facilities





**TASKI®**

**Strip Eze**



**F1**

## Stripper

### Directions for use

1. Dust, mop with or sweep to remove dust or dirt.
2. Dilute 1 part TASKI® Strip Eze with 2 -6 parts of cool water depending on build up.
3. Apply liberal amounts of solution to the surface to be stripped.
4. Let stripper solution soak in for 5-7 minutes. Keep areas to be stripped wet.
5. Agitate surface thoroughly using mop or swing machine using a stripping pad or brush to break up film.
6. Manually strip areas that cannot be reached with the machine.
7. Pick-up all of the solution with a clean mop, wet vac or autoscrubber. Trail mop as needed if stripper residues are present.
8. Rinse floor with clean water using clean mop and bucket or auto scrubber if stripper residues are present.
9. Let floor dry completely.
10. Inspect floor for any areas requiring further stripping.
11. Wash out all equipment before storage.

Technical data			
Appearance	Clear liquid	Odour	Characteristic odour
pH (concentrate)	13.5	pH (1:2)	13.0
Specific Gravity (20°C)	1.06	Dilution	1:6 (Light build up), 1:2 (Heavy build up)
Coverage	Approx. 20 – 50m <sup>2</sup> per litre, depending on build up		

*The above data is typical of normal production and should not be taken as a specification.*

Product	Pack size	SKU Code	Availability
TASKI® Strip Eze	2 x 5L	5487081	AU & NZ

### Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet. Store in original container. Avoid extremes of temperature and humidity.

### Product compatibility

Under recommended conditions of use, TASKI® Strip Eze is suitable on most floor types. Not suitable on linoleum, rubber and wooden floors.

### Safety Reminder

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available online at [www.diversey.com](http://www.diversey.com) or by calling Toll free: Australia, 1800 647 779 or New Zealand, 0800 803 615.

For additional information, please contact us at:

Diversey Australia Pty Ltd Toll free: 1800 647 779, Diversey New Zealand Ltd Toll free: 0800 803 615 [www.diversey.com](http://www.diversey.com).

Legal disclaimer: The associated products or services are manufactured by or otherwise emanate from Diversey Companies and their subsidiaries and not from Sealed Air.