

Product Data Sheet

Product Code: TRU

Issued: February 25, 2011

What is Truckwash?

TRUCKWASH is a powerful cleaner for removing road dirt, oil and carbon from truck, car and bus paintwork, rubber, chrome and glass.

Key Benefits

- ✓ Effective removal of traffic film and road dirt.
- ✓ Will not dull the paintwork.
- ✓ Will not cause rusting. Contains corrosion inhibitor.
- ✓ Leaves tyres clean and black.
- ✓ Dries streak-free.

How Does It Work?

TRUCKWASH is a concentrated vehicle detergent for breaking down and removing road dirt, mud, oil films, exhaust soot and insect residues from most vehicles.

For Use On...

TRUCKWASH is to be used on trucks, cars, 4WD's, caravans, boats, motorbikes, trains and trams. It is effective for cleaning paintwork, rubber trims and tyres, chrome, aluminium, glass, mag wheels, fibre glass and vinyl surfaces.

Because of its great versatility, TRUCKWASH is also ideal for cleaning exterior hard surfaces exposed to road grime and the elements, such as brickwork, walls, canopies, blinds, roof tiles, paintwork and windows.

TRUCKWASH may be used with soft or hard water. It is a 'Quick Break' detergent, allowing total segregation of oil and water.

Technical Data

Composition

TRUCKWASH is nearly pH-neutral. It contains natural and synthetic surfactants, sequestrants, builders, corrosion inhibitor and water.

Properties

COLOUR – Bright blue liquid

ODOUR – None

pH = 7.5 – 8.5

FOAM – High foam of moderate stability



Environmental Care



TRUCKWASH conforms with all statutory environmental requirements. It is based on safe ingredients selected to perform efficiently so there is no waste or damage. TRUCKWASH is non-flammable and biodegradable. TRUCKWASH containers will be cleaned and reused if returned to Agar Cleaning Systems Pty Ltd., significantly reducing plastic usage and waste. They can also be recycled.

Quality

The design, manufacture and supply of all Agar chemical products is controlled by the Agar Quality Management System which is registered and externally audited by SAI Global as complying with the requirements of AS/NZS ISO 9001 "Quality Management Systems – Requirements".

First Certified: 30 April 1996

SAI Certificate No.: QEC7358

Application

- It is best to use TRUCKWASH on cool surfaces (i.e. in the shade, if possible).
- Hose down the surfaces to remove excess dirt and dust particles.
- Dilute TRUCKWASH to 1 in 10 (for heavy soil or foam-gun application) or 1 in 20 (for light soil or brush-on application).
- Spray or brush the solution over all surfaces until completely wet, working from the bottom upwards.
- Allow to soak for 5 to 15 minutes so the TRUCKWASH can break down the dirt. It is okay if the solution dries out on the surface.
- Rinse off with a hose or pressure washer to remove all of the dirt and detergent.
- To remove baked-on dirt or bug splatters use TRUCKWASH straight from the bottle on to a soft cloth.

Agar Cleaning Systems maintains Safety Data Sheets (SDS) on all of its products. These sheets contain information that you may need to protect your employees and customers against health or safety hazards associated with our product. Agar Cleaning Systems recommends that you obtain a copy of the respective SDS sheet prior to using this product. The information in the Product Data Sheet is based on data we believe to be reliable. It is offered in good faith, but without guarantee, as conditions and methods of use of our product are beyond our control.