

Product Data Sheet

Product Code: SUPN

Issued: August 25, 2023

What is SUPER NOVA?

SUPER NOVA is a super-glossy, rock-hard polish which is the corner-stone of the Agar no-buff system. It is designed for sealing vinyl, timber and terrazzo floors.

Key Benefits

- ✓ Made with innovative polymer technology to form a tough film that holds its shine even without buffing.
- ✓ Will not discolour.
- ✓ Is non-slip.
- ✓ Will dramatically lift the standard of shine on floors that receive minimal maintenance.
- ✓ Is designed to save time and money.

How Does It Work?

SUPER NOVA is a super-glossy, rock-hard polish that is so tough and mark-resistant that it holds its shine even without buffing, yet it will respond well to being buffed.

For Use On...

SUPER NOVA is a non-slip polish for vinyl, sealed timber and terrazzo floors. Because it repels scuffs, scratches and traffic marks and lasts exceptionally well, SUPER NOVA is ideal for use on floors that are not buffed. In fact, floors can be maintained without a buffing machine when SUPER NOVA is used.

Technical Data

Properties



COLOUR – Milky white liquid
ODOUR – Faint ammonia odour
pH = 8.3 – 9.5

COVERAGE: 40 - 50 sq metres per litre

Environmental Care



SUPER NOVA conforms with all statutory environmental requirements. It is based on safe ingredients selected to perform efficiently so there is no waste or damage. SUPER NOVA is non-flammable. SUPER NOVA containers will be cleaned and reused if returned to Agar Cleaning Systems Pty Ltd., significantly reducing plastic usage and waste. They can also be recycled.

VOC Content:

SUPER NOVA contains less than 2 grams of Volatile Organic Compounds per litre. SUPER NOVA therefore

complies with “green” standards which require the VOC content to be less than 7% (i.e., 70 grams per litre).

Quality

The design, manufacture and supply of all Agar chemical products is controlled by the Agar Quality Management System which is registered and externally audited by SAI Global as complying with the requirements of AS/NZS ISO 9001 “Quality Management Systems – Requirements”.

First Certified: 30 April 1996

SAI Certificate No.: QEC7358

Slip Resistance

SUPER NOVA passes the Slip Resistance Test under dry conditions as specified in AS 4663-2013. It gives a mean Dynamic Coefficient of friction of 0.75.

Application

- Remove adhesive, built-up polish or wax and other soilage using ULTRASTRIP, DEMOLISH or STR-36. New floors should always be stripped prior to sealing. Whilst a new floor looks clean, it is covered in a protective film added at the time of manufacture. New floor polish will not adhere to this film, so it must be stripped.
- Rinse floor, allow to dry, then fringe-mop to remove dust.
- Mop on 2-5 coats of SUPER NOVA allowing 20-30 minutes to dry between coats, then allow to harden overnight.
- Maintain floor by cleaning with AUTOSCRUB. If the gloss wears down after a period of several weeks, clean the floor then apply another coat of SUPER NOVA.
- After six months, the floor may need to be stripped so the coating may be renewed.
- Do not apply any polish to a very cold floor (9°C or less).

Available in: 5L, 20L

Agar Cleaning Systems maintains Safety Data Sheets (SDS) on all of its products. These sheets contain information that you may need to protect your employees and customers against health or safety hazards associated with our product. Agar Cleaning Systems recommends that you obtain a copy of the respective SDS sheet prior to using this product. The information in the Product Data Sheet is based on data we believe to be reliable. It is offered in good faith, but without guarantee, as conditions and methods of use of our product are beyond our control.