

Product Data Sheet

SoSafe™ Green Graffiti Remover – Broad Spectrum posters, gum and graffiti remover

Ideal to remove graffiti, posters and gum from a broad range of surfaces including painted surfaces, plastics, bricks, powdercoated surfaces, playground equipment, shutters, bus interiors and many other surfaces.

Product Description

SoSafe™ Green graffiti remover for removal of bill posters, gum and graffiti is a broad-spectrum graffiti remover ideal for use on surfaces to remove spray paint, marker, poster glue, shoe polish, chewing gum and crayon.

SoSafe™ Green is popular with Californian government departments, as it contains no proposition 65 chemicals. SoSafe™ Green can be used in conjunction with or without high-pressure equipment depending on the graffiti and substrate at hand.

Characteristics

- * pH Neutral
- * Non-Flammable
- * Non-Hazardous
- * Non-Toxic
- * Non-Corrosive
- * Biodegradable

Tools / Equipment

- * Gloves
- * Graffiti Remover
- * Scourer / Nylon Brush
- * Applicator (Sprayer / Paint Brush / Roller)
- * Water Bucket / Hose
- * Chemical Goggles
- * White Rag

Safety

When using graffiti remover follow safety directions on the label, wear appropriate attire including - enclosed shoes, gloves and non-vented goggles.

Application Procedure

1. Apply graffiti removing product by sprayer, paint brush or roller.
2. Wait a minimum of 30 second for painted surfaces.
3. Rub surface with a scourer or rag in a circular motion. If the graffiti moves, the bond between the graffiti and the surface is breaking, if not allow additional time. To remove, wipe the surface clean then rinse wall with water.
4. Rub surface softly with a scourer or rag in a circular motion. If the graffiti moves, the bond between the graffiti and the surface is breaking, if not allow additional time. To remove, wipe the surface clean then rinse wall with water.
5. If shadow remains repeat steps 2 to 4.

Product Coverage

Coverage rates for graffiti removal vary significantly depending on various factors such as: age of the graffiti, type of graffiti, thickness of the graffiti, temperature, moisture, porosity, substrate and equipment used. A typical spray paint tag 1 metre x 2 metres on a colorbond fence will require approximately 100mLs to 1 Litre of product.

Pack Sizes

12x 750mL / 3x5Lt / 25Lt

Disclaimer

To the best of our knowledge and belief, the information is true and accurate at the time of publication. Since the conditions of use are out of the agents/distributors/manufacturers control, the end user must satisfy themselves by prior testing the product is suitable for their specific

SoSafe Specialty Products Pty Limited ABN 73 001 553 699
Postal: PO Box 386, Brookvale NSW 2100 Australia
Phone: (+612) 9938 1800
Fax: (+612) 9905 0979
Email: sales@sosafe.com.au
Web: www.sosafe.com.au