Product Information Sheet



STEAMROLLER II

Heavy Duty Floor Stripper



Product

- ✓ Aggressive stripping action to reduce scrubbing time
- ✓ Pleasant pine aroma
- ✓ Incredibly fast penetration to suspend the sealer from the floor
- ✓ Totally solubilises polish into a clear jelly liquid
- ✓ No ammonia or "nasty" chemicals smells

Extra heavy-duty floor stripper for difficult and hard to remove sealers including water-based finishes, concrete sealer and urethane fortified acrylic sealers. Product must be applied, given time to activate, scrubbed and then rinsed off using neutraliser to counteract the alkalinity, particularly on stone/terrazzo surfaces. Ideal for use with gas stripping machines and auto scrubbers over large areas.

Technical

Colour	Yellow	Product Code	Description	Outer Pack	APN
Odour	Pine	165211	CHRC-26015A Steamroller II 5L	3	9324828002345
рH	12.50 – 13.50	·			
Dangerous G	oods Classification				
ADG CODE	1719				
DG Class	8, Corrosive Substances				
PACK GRP	III	CORROSIVE			
HAZCHEM	2R	8			

Application

Floor Stripping	Method				
Dilution rate:	Prepare the correct dilution according to finish build up.				
	2. Generously spread the floor stripping solution over area with mop and bucket.				
General build-up:	3. Allow the solution to work on the floor for 5-10 mins (usually at least 5 minutes). Do not				
1 to 8 parts warm water	allow the stripping solution to dry.				
	4. Place Oates Floormaster black heavy-duty stripping pad under the floor machine or use the				
Heavy build-up:	stripping brush. For terrazzo use Tynex brushes to help cut through heavy build up				
1 to 4 parts warm water	5. Scrub length wise along skirting boards. Then strip side to side over the remaining area.				
	6. Use the hand scrub pad to detail strip along the edges and in the corners of the room. Heel				
	the floor machine on badly soiled spots. Avoid splashing stripper on walls.				
	7. Work in a controlled area to avoid walking on the wet area.				
	8. Use a wet pick-up vacuum to remove stripper solution from the floor.				
	9. Do not allow the dirty solution to dry on the floor.				
	10. Use a clean mop and clean water. Cover area liberally with rinse water.				
	11. Pick up the rinse water with the wet pick-up vacuum. Wipe all skirting boards before they				
	dry.				
	12. Damp mop the floor with clear water for the final rinse and to ensure that all stripper				
	solution has been removed.				

ersion: 4 Page 1 of 2

Research Products recommends you obtain and read the Safety Data Sheet (SDS) before using any product, available from www.oateslaboratories.com.au.

This Product Information Sheet is offered without guarantee as the conditions and method of application of this product are beyond our control.



FREUDENBERG HOME & CLEANING SOLUTIONS PTY LTD

ABN 99 082 274 324

13-21 Maygar Boulevard, Broadmeadows VIC 3047

Customer Service: 1300 669 686 | Website: www.oateslaboratories.com.au

Product Information Sheet



STEAMROLLER II

Heavy Duty Floor Stripper



Hazard Statement

H290: Corrosive to metals.

H302: Harmful if swallowed.

H332: Harmful if inhaled.

H314: Causes severe skin burns and eye damage.

H402: Harmful to aquatic life.

Prevention

P102: Keep out of reach of children.

P260: Do not breathe fumes, mists, vapours or spray.

P264: Wash contacted areas thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P280: Wear protective gloves, protective clothing and eye or face protection.



Version: 4

Page 2 of 2

Research Products recommends you obtain and read the Safety Data Sheet (SDS) before using any product, available from www.oateslaboratories.com.au.

This Product Information Sheet is offered without guarantee as the conditions and method of application of this product are beyond our control.

